



VP-22/28

High Reliability

- High efficient oil mist filters contribute to solve the issues of oil exhaust and smoking as well as prolong the service life.
- Sealing parts are made from fluororubber, which improved the performance of anti-corrosion and solved oil leakage issues.
- Multiple shifts design for gas ballast to meet customers' demand of ultimate vacuum and capability of vapor evacuation.
- Horizontal CNC machining of Japanese Mori Seiki guarantees high reliability.
- Unique industrial design generated elegant appearance.

Specifications

Model		VP-22	
Displacement speed	m ³ /h	22	
Ultimate pressure	Without gas ballast	mbar	≤0.3
	With gas ballast I	mbar	≤0.5
	With gas ballast II	mbar	≤2.5
Water vapor tolerance	With gas ballast I	mbar	15
	With gas ballast II	mbar	30
Noise level	dB	≤58	
Power supply		Single/Three-Ph	
Power rating	kW	1.1	
Motor speed (50/60Hz)	rpm	1440/1720	
Ambient temperature	°C	10 - 40	
Oil capacity	L	1	
Level of protection		IP54	
Intake and exhaust		G3/4"	
Weight	Kg	30	
Dimension (L*W*H)	mm	496×268×248	

Specifications

Model		VP-28	
Displacement speed	m ³ /h	28	
Ultimate pressure	Without gas ballast	mbar	≤0.3
	With gas ballast I	mbar	≤0.5
	With gas ballast II	mbar	≤2.5
Water vapor tolerance	With gas ballast I	mbar	15
	With gas ballast II	mbar	30
Noise level	dB	≤58	
Power supply		Single/Three-Ph	
Power rating	kW	1.1	
Motor speed (50/60Hz)	rpm	1440/1720	
Ambient temperature	°C	10 - 40	
Oil capacity	L	1	
Level of protection		IP54	
Intake and exhaust		G3/4"	
Weight	Kg	30	
Dimension (L*W*H)	mm	496×268×248	