

HIGH-EFFICIENCY INDUSTRIAL CLEANING

INDUSTRIAL VACUUM
CLEANER

CY3850 WAS AVAILABLE IN BOTH PLASTIC AND STAINLESS STEEL SERIES. THE STAINLESS STEEL SERIES CAN BE EQUIPPED WITH A FIXED VACUUM FLOOR TOOL. WITH THE TOOL, CY3850 CAN BE PUSHED AND SUCKED AT THE SAME TIME. IT IS SUITABLE IN AN INDUSTRIAL ENVIRONMENT WITH AN AREA OF LESS THAN 2000 SQUARE METERS, SUCH AS FACTORIES, WORKSHOPS, WAREHOUSES, SHOPPING MALLS, CLUBS, ETC. IT CAN ABSORB OBJECTS SUCH AS DUST, POWDER, GLASS, IRON FILINGS, WATER, STEEL GRIT, ETC.



60 L COLLECTION TANK

BUILT FOR PRODUCTIVITY Powerful pickup. Flexible configuration. Easy daily operation.

CORE COMPONENTS

PERFORMANCE ENGINEERED



ELECTRIC MOTOR
Industrial-grade motors deliver strong, continuous suction.



HEPA FILTRATION
High-efficiency filtration captures fine airborne dust.



STANDARD ACCESSORIES
Complete tool kit for floor, corner and equipment cleaning.



PUSH-SUCK FLOOR BRUSH
Push and vacuum floors in a single pass.

TECHNICAL SPECIFICATIONS

CY3850 CONFIGURATION

PARAMETER	UNIT	CY3850
VOLTS	V/HZ	220/50
POWER	W	3600
SUCTION	KPA	26
AIRFLOW	M3/H	540
FILTERAERA	cm2	24000
FILTERCLEANING METHOD	—	MAUNAL BLOWBACK
NOISE	DB(A)	69
SUCTION DIAMETER	MM	40
VOLUME	L	60
WEIGHT	KG	28
DIMENSIONS	MM	550*500*1100

Specifications subject to change without notice.