

HIGH-EFFICIENCY INDUSTRIAL CLEANING

INDUSTRIAL VACUUM
CLEANER

ADOPTING AMETEK TURBO MOTOR, IT HAS STRONG AND CONTINUOUS SUCTION. THE MOTOR HAS UNDERGONE NOISE REDUCTION TREATMENT. THE EQUIPMENT IS MAINLY USED FOR SUPPORTING DEVICES CONTINUOUS USE OF ASSEMBLY LINES AND FIXED WORK AREAS. IT IS CUSTOMIZABLE FOR ENVIRONMENTS, SUCH AS CARVING MACHINES, FOOD AND PHARMACEUTICAL ASSEMBLY LINES, MACHINING, ETC.



CONTINUOUS DUTY

BUILT FOR
PRODUCTIVITY

Powerful pickup. Flexible configuration.
Easy daily operation.

CORE COMPONENTS



HEPA FILTRATION
High-efficiency filtration captures fine airborne dust.



ELECTRIC MOTOR
Industrial-grade motors deliver strong, continuous suction.

STANDARD ACCESSORIES



STANDARD ACCESSORIES
Complete tool kit for floor, corner and equipment cleaning.

PERFORMANCE ENGINEERED



BLOWBACK DEVICE
On-board pulse cleaning keeps the filter working efficiently.

TECHNICAL SPECIFICATIONS

CY80SC CONFIGURATION

PARAMETER	UNIT	CY80SC/2.2	CY80SC/3.0	CY80SC/4.0	CY80SC/5.5	CY80SC/7.5
VOLTS	V/HZ	380/50	380/50	380/50	380/50	380/50
POWER	KW	2.2	3.0	4.0	5.5	7.5
SUCTION	KPA	22	26	28	32	34
AIRFLOW	M3/H	320	380	410	530	540
CLEANING METHOD	—	MANUAL BLOWBACK				
FILTER AREA	cm2	35000	35000	35000	35000	35000
NOISE	DB(A)	64	69	69	70	70
SUCTION DIAMETER	MM	40-63	40-63	40-63	40-80	40-80
VOLUME	L	80	80	80	80	80
WEIGHT	KG	83	90	98	140	145
DIMENSIONS	MM	1050X590X 1050				

Specifications subject to change without notice.