

HIGH-EFFICIENCY INDUSTRIAL CLEANING

FLOOR SANDING DUST EXTRACTION UNIT

THE CYYM420 SERIES CAN WORK CONTINUOUSLY FOR A LONG TIME WITHOUT STOPPING, IT IS A CORE ENVIRONMENTAL PROTECTION EQUIPMENT IN FLOOR SANDING OPERATIONS. IT PRODUCES ULTRAFINE POWDER DURING THE SANDING OF HARD FLOORS SUCH AS CONCRETE AND EPOXY RESIN PROVIDE A SYSTEMATIC DUST REMOVAL SOLUTION, THE VACUUM CLEANER COMES WITH A PULSE BLOWBACK SYSTEM, WHICH



BUILT FOR PRODUCTIVITY

Powerful pickup. Flexible configuration. Easy daily operation.

CORE COMPONENTS

PERFORMANCE ENGINEERED



HEPA FILTRATION

High-efficiency filtration captures fine airborne dust.



ELECTRIC MOTOR

Engineered component for reliable daily operation.



STANDARD ACCESSORIES

Complete tool kit for floor, corner and equipment cleaning.



SOFT START CONTROL

Engineered component for reliable daily operation.

TECHNICAL SPECIFICATIONS

CYYM420 CONFIGURATION

PARAMETER	UNIT	CYYM420/2.2	CYYM420/3.0	CYYM420/4.0	CYYM420/5.5	CYYM420/7.5
VOLTS	V/Hz	380/50	380/50	380/50	380/50	380/50
POWER	KW	2.2	3.0	4.0	5.5	7.5
SUCTION	KPA	22	26	28	32	34
AIRFLOW	M3/H	320	380	410	530	540
CLEANING METHOD	—	AUTOMATIC PULSE BLOWBACK				
FILTER AREA	cm2	81000	81000	81000	81000	81000
NOISE	DB(A)	64	69	69	70	70
SUCTION DIAMETER	MM	40-63	40-63	40-63	40-80	40-80
VOLUME	L	60-120	60-120	60-120	60-120	60-120
WEIGHT	KG	135	140	143	170	175
DIMENSIONS	MM	1150*600*1750				

Specifications subject to change without notice.