

HIGH-EFFICIENCY INDUSTRIAL CLEANING

# DUAL-BARREL INDUSTRIAL VACUUM CLEANER

The YMSTZD series works continuously for long periods with a dual-barrel design. The front barrel separates large amounts of dust, reducing the working pressure on the filter.

It provides a systematic dust-removal solution for the ultra-fine powder generated during floor sanding.

**BUILT FOR PRODUCTIVITY**

Powerful pickup. Flexible configuration. Easy daily operation.



## CORE COMPONENTS



**HEPA FILTRATION**

High-efficiency filtration captures fine airborne dust.



**ELECTRIC MOTOR**

Industrial-grade motors deliver strong, continuous suction.



**STANDARD ACCESSORIES**

Complete tool kit for floor, corner and equipment cleaning.



**SOFT START CONTROL**

Soft start protects the motor and extends service life.

PERFORMANCE ENGINEERED

## TECHNICAL SPECIFICATIONS

YMSTZD CONFIGURATION

| PARAMETER        | UNIT  | YMSTZD/2.2              | YMSTZD/3.0 | YMSTZD/4.0 | YMSTZD/5.5 | YMSTZD/7.5 |
|------------------|-------|-------------------------|------------|------------|------------|------------|
| VOLTS            | V/Hz  | 380/50                  | 380/50     | 380/50     | 380/50     | 380/50     |
| POWER            | KW    | 2.2                     | 3.0        | 4.0        | 5.5        | 7.5        |
| SUCTION          | KPA   | 22                      | 26         | 28         | 32         | 34         |
| AIRFLOW          | M3/H  | 320                     | 380        | 410        | 530        | 540        |
| CLEANING METHOD  | —     | AUTOMATIC PULS BLOWBACK |            |            |            |            |
| FILTER AREA      | cm2   | 81000                   | 81000      | 81000      | 81000      | 81000      |
| NOISE            | DB(A) | 64                      | 69         | 69         | 70         | 70         |
| SUCTION DIAMETER | MM    | 40-63                   | 40-63      | 40-63      | 40-80      | 40-80      |
| VOLUME           | L     | 100                     | 100        | 100        | 100        | 100        |
| WEIGHT           | KG    | 131                     | 138        | 146        | 193        | 198        |
| DIMENSIONS       | MM    | 1500*600*1750           |            |            |            |            |

\*Specifications subject to change without notice.\*